

Material Safety Data Sheet

Prepared 2/11/2004

Section VII HEALTH INFORMATION

EYE CONTACT: Product may cause severe irritation and corneal trauma up to and including blindness.

SKIN CONTACT: Moderately irritating to the skin – prolonged contact may harm the skin.

INHALATION: Product may be irritating to the throat, nose, and/or respiratory tract. Prolonged exposure may damage the lungs.

INGESTION: Ingestion of excessive amounts may cause drowsiness, dizziness, headache, and/or fatigue. Product may cause irritation to the gastrointestinal tract through consumption including damage to mucous membranes.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing conditions (such as eye, skin, and respiratory disorders) may be aggravated through exposure of this material.

OTHER HEALTH EFFECTS: None known.

Section VIII EMERGENCY/FIRST AID PROCEDURES

EYE CONTACT: Move victim to an area with fresh air and flush the eyes for at least 15 minutes with water. Seek medical help immediately.

SKIN CONTACT: Remove any contaminated clothing and wash exposed skin with soap and water. Seek medical attention.

INHALATION: Move victim to an area with fresh air and away from the material. If breathing problems develop and/or irritation continues, have a qualified person administer oxygen and contact a physician immediately. If the victim is not breathing, perform artificial respiration and seek immediate medical attention.

INGESTION: Have victim drink water or milk to dilute unless the victim is unconscious. Transport the victim to emergency facilities immediately.

Section IX PERSONAL PROTECTION

CLOTHING: Cover eyes with safety glasses/goggles or splash shield. Do not wear contact lenses. Handlers should also wear long sleeves, pants that cover entire legs, and gloves to prevent skin exposure.

BREATHING: Handlers should use this product in well-ventilated areas to prevent exposure to higher vapor concentrations. Use appropriate NIOSH approved respirator if exposure exceeds the PEL/TLV.

Section X ENVIRONMENTAL INFORMATION

SPILLS: Clear area of all personnel not wearing appropriate protective gear (including respirator). Dike and contain. Stop the leak. Water fog will suppress any vapor cloud that forms. Remove with vacuum or pump equipment. Use absorbent media for remaining residue. Trace residue can be removed from site with a clean water flush. Observe all pertinent local, state and federal regulations on disposal of water-based chemical compounds.