MATERIAL SAFETY DATA SHEET

ACRYLIC CURE AND SEAL No. CHLQ-007.M

Manufacturer: RIGHT/POINTE COMPANY
Address: 234 Harvestore Drive
DeKalb, IL 60115
Telephone: 815/754-5700
Fax: 815/754-5702

H.M.I.S.

Health: 1 **Flammability: 2**
Reactivity: 0 **Personal Protection:**
Hazard Rating: 0=least, 1-slight, 2=moderate, 3=high, 4=extreme, *=chronic

SECTION 1: Ingredients and Hazards	**%**	**Exposure Limits**
Mineral Spirits:	82	OSHA: PEL/TWA: 100ppm ACGIH: TLV/TWA: 100ppm

SECTION 2: Physical Data

Solubility in Water:	Nil
Specific Gravity:	(H2O=1): .88
Appearance and Odor:	Amber liquid, petroleum odor.
Boiling Point:	310°F
Vapor Density:	(Air=1): 4.9
Evaporation Rate:	(Butyl acetate=1): <1
Vapor Pressure:	(mm HG): 2@68°F
% Volatile (by wt):	68

SECTION 3: Fire and Explosion Data

Flash Point and Method:	>105°F
Autoignition Temperature:	ND
Extinguishing Media:	Water, Foam, Dry chemical, CO2, Fog
Unusual Fire/Explosion Hazards:	Vapors can travel to source of ignition and flash back.
Special Fire Fighting Procedure:	Wear a Self-Contained Breathing Apparatus (SCUBA) (pressure-demand, MSHA/NIOSH-approved or equivalent) and full protective gear. Use water spray to cool.
Lower/Upper Explosion Limit:	1.0%/6.0% est.

SECTION 4: Reactivity Data

Avoid contacting with strong oxidizers.

SECTION 5: Health Hazard Information

Stability:	Stable
Hazardous Decomposition Products:	In presence of air may yield Carbon Dioxide and /or Carbon Monoxide.
Hazardous Polymerization:	Will not occur.