



**EverLastic™**  
**Acrylic Crack Sealant**

**Description:**

EverLastic™ Acrylic Crack Sealant is a blend of acrylic copolymers and reinforcing fillers specifically formulated to outperform traditional asphalt based crack fillers. EverLastic™ is a cold applied, pourable crack sealant that exhibits excellent cold weather performance. With its acrylic resin base, EverLastic™ delivers long term flexibility over a wide range of temperatures and sets quickly with less shrinkage, thereby allowing pavement sealer to be applied sooner than with traditional asphalt based crack fillers.

**Application:**

EverLastic™ Acrylic Crack Sealant can be applied just like traditional asphalt based crack fillers and is compatible with Brewer Cote® and Eclipse® pavement sealers.

EverLastic™ can be used to fill cracks up to 1/2 " in width, on either asphalt or concrete pavements. EverLastic™ must be applied only to cracks that are clean, dry and free of debris and weeds. All vegetation must be treated with a water based herbicide at least one (1) week prior to crack sealing to prevent re-growth.

Use EverLastic™ full strength. Do not dilute. Thoroughly mix EverLastic™ prior to and during application. Fill the cracks with EverLastic™, making sure to squeegee any excess material flush with the pavement surface. Allow EverLastic™ to cure before sealing or striping.

EverLastic™ must be applied only when ambient and pavement temperatures are a minimum of 50 °F and are expected to remain there for at least eight (8) hours after application.

**Everlastic™ Typical Properties:**

Property	Typical
Elongation, % @ 32 °F	200
Recovery, % @ 32 °F	95
Non-Volatile, %	73 - 76
Flow @ 140 °F, mm	0
Gasoline Resistance	Pass - 24 hr. immersion
1000 Hrs. Artificial Weathering	No cracking, adhesion loss or blistering
Cured Color	Black

**Key Advantages**

- Ready to use
- Remains flexible over a broad temperature range
- Minimal shrinkage
- Fast drying
- Scuff and mar resistant
- Fuel resistant
- Dark black color

**Coverage:**

One gallon of EverLastic™ Acrylic Crack Sealant will fill the following number of lineal feet:

Width	Depth		
	1/8"	1/4"	1/2"
1/8"	1200	600	300
1/4"	600	300	150
1/2"	300	150	75

**Precautions:**

EverLastic™ Acrylic Crack Sealant may cause minor skin irritation. As with all chemicals, wear splash resistant goggles, protective gloves and clothing when handling EverLastic™. In case of skin or eye contact, immediately flush the area with clean water. Consult Material Safety Data Sheet for more information on safety and handling.

- |   |   |
|---|---|
| <p><b>Keep out of reach of children</b><br/><b>For exterior use only</b><br/><b>Close container when not in use</b></p> | <p><b>Protect from freezing</b><br/><b>Do not dilute</b><br/><b>Non-flammable</b></p> |
|---|---|

**Packaging:**

1 gallon pour spout jug (6 per case) and 5 gallon pails

**Limited Warranty:**

The Brewer Company warrants this product to be of merchantable quality when stored, used, and applied in accordance with the specifications and instructions herein. This Limited Warranty represents the sole and exclusive warranty. The Brewer Company's liability under this Limited Warranty is limited to replacement of the product proven defective, or at its option, refund of the purchase price.